

GENESIS® ToiVac N

Flexible and very heavy weight ducting made of PE, with tightly welded connection cuffs

Applications	mobile toilets, sewage suction, waste disposal vehicles, waste water, sewage treatment plants
Structure	PE, yellow / saffron yellow (similar RAL 1017), opaque, plastic spiral / PE
Temperature	-40°C up to 60°C
Properties	can be driven over, crush-resistant, good tensile strength, very high vacuum resistance, very good chemical resistance, weather proof, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof



Inner Diameter (mm)	Wall Thickness (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	1,30	0,95	9,49	10	43511051-1000-130-00
51	1,30	0,95	14,16	15	43511051-1500-130-00
51	1,30	0,95	17,23	18,3	43511051-1830-130-00
51	1,30	0,95	18,82	20	43511051-2000-130-00
51	1,30	0,95	23,49	25	43511051-2500-130-00
76	1,30	0,95	13,94	10	43511076-1000-130-00
76	1,30	0,95	20,76	15	43511076-1500-130-00
76	1,30	0,95	25,26	18,3	43511076-1830-130-00
76	1,30	0,95	27,57	20	43511076-2000-130-00
102	1,30	0,85	17,69	10	43511102-1000-130-00
102	1,30	0,85	26,32	15	43511102-1500-130-00