Ocono
Ruhrkunststoff

FLEXADUX® HT 1100 CL

Highly flexible clip-on hose for temperatures up to +1100°C




Applications exhaust gas extraction, extraction systems, high temperature applications, automotive engineering

Structure high temperature stainless steel fabric, grey / silver grey (similar RAL 7001), opaque, clip profile / multi-layer

Temperature -50°C up to 1.100°C

Properties good flexibility, excellent temperature resistance, with external abrasion protection spiral, flame-retardant





made in Germany

Inner Diameter (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
102	60	0,20	3,60	3	53323102-0300-000-00
152	90	0,09	4,90	3	53323152-0300-000-00
160	96	0,08	5,10	3	53323160-0300-000-00
200	120	0,05	13,20	6	53323200-0600-000-00
203	120	0,05	6,60	3	53323203-0300-000-00
203	120	0,05	13,20	6	53323203-0600-000-00
250	175	0,04	9,00	3	53323250-0300-000-00
250	175	0,04	18,00	6	53323250-0600-000-00
254	175	0,04	9,00	3	53323254-0300-000-00
305	210	0,02	11,70	3	53323305-0300-000-00
350	245	0,02	13,80	3	53323350-0300-000-00
407	280	0,01	17,40	3	53323407-0300-000-00
508	400	0,01	22,80	3	53323508-0300-000-00

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 04.11.2026