# FLEXADUX® HYP T EL CL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive



| | |
|---|---|
| **Applications** | paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, air extraction |
| **Structure** | Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / multi-layer |
| **Temperature** | -40°C up to 175°C, short term up to 190°C |
| **Properties** | light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive |
| **Norms** | TRBS 2153, ATEX 2014/34/EU |







made in Germany

| Inner Diameter (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---|---|---|---|---|---|---|
| 50 | 30 | 0,90 | 0,40 | 2,40 | 6 | 53319050-0600-000-00 |
| 60 | 36 | 0,78 | 0,28 | 3,00 | 6 | 53319060-0600-000-00 |
| 70 | 42 | 0,67 | 0,20 | 3,50 | 6 | 53319070-0600-000-00 |
| 80 | 48 | 0,61 | 1,56 | 3,60 | 6 | 53319080-0600-000-00 |
| 90 | 54 | 0,56 | 0,12 | 3,70 | 6 | 53319090-0600-000-00 |
| 102 | 60 | 0,51 | 0,10 | 3,75 | 6 | 53319102-0600-000-00 |
| 110 | 66 | 0,48 | 0,08 | 4,20 | 6 | 53319110-0600-000-00 |
| 127 | 75 | 0,33 | 0,06 | 4,80 | 6 | 53319127-0600-000-00 |
| 140 | 84 | 0,25 | 0,05 | 5,10 | 6 | 53319140-0600-000-00 |
| 152 | 90 | 0,22 | 0,04 | 2,70 | 3 | 53319152-0300-000-00 |
| 152 | 90 | 0,22 | 0,04 | 5,40 | 6 | 53319152-0600-000-00 |
| 160 | 96 | 0,21 | 0,04 | 3,00 | 3 | 53319160-0300-000-00 |
| 160 | 96 | 0,21 | 0,04 | 6,00 | 6 | 53319160-0600-000-00 |
| 180 | 108 | 0,17 | 0,03 | 6,60 | 6 | 53319180-0600-000-00 |



Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026