Ocono
Ruhrkunststoff

FLEXADUX® P 2 HL

Light weight and flexible spiral hose made of PVC-coated polyester fabric, antistatic



Applications paint mist extraction, solvent vapor extraction, air conditioning & HVAC, air extraction, extraction systems

Structure PVC coated polyester fabric, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / not coated / copper plated

Temperature -40°C up to 80°C

Properties good flexibility, very good low-temperature flexibility, very good chemical resistance, flame-retardant, permanently antistatic (R ≤ 10^8 Ohm)

Norms flame-retardant according to DIN 4102 / B1 | TRGS 727





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
25	29,00	0,40	25	2,00	0,35	1,37	10	24005025-1000-000-99
25	29,00	0,40	25	2,00	0,35	2,05	15	24005025-1500-000-99
30	34,00	0,40	30	1,80	0,32	1,62	10	24005030-1000-000-99
30	34,00	0,40	30	1,80	0,32	2,43	15	24005030-1500-000-99
40	44,00	0,40	40	1,50	0,30	3,41	15	24005040-1500-000-99
40	44,00	0,40	40	1,50	0,30	2,27	10	24005040-1000-000-99
50	54,00	0,40	50	1,20	0,25	2,81	10	24005050-1000-000-99
50	54,00	0,40	50	1,20	0,25	4,21	15	24005050-1500-000-99
60	64,00	0,40	60	1,00	0,20	3,34	10	24005060-1000-000-99
60	64,00	0,40	60	1,00	0,20	5,02	15	24005060-1500-000-99
70	74,00	0,40	70	0,90	0,18	3,88	10	24005070-1000-000-99
70	74,00	0,40	70	0,90	0,18	5,82	15	24005070-1500-000-99
75	79,00	0,40	75	0,85	0,12	4,15	10	24005075-1000-000-99
75	79,00	0,40	75	0,85	0,12	6,22	15	24005075-1500-000-99
80	84,00	0,40	80	0,80	0,10	4,42	10	24005080-1000-000-99
80	84,00	0,40	80	0,80	0,10	6,63	15	24005080-1500-000-99
90	94,00	0,40	90	0,70	0,09	4,95	10	24005090-1000-000-99
90	94,00	0,40	90	0,70	0,09	7,43	15	24005090-1500-000-99
100	105,00	0,40	100	0,60	0,08	5,32	10	24005100-1000-000-99
100	105,00	0,40	100	0,60	0,08	7,98	15	24005100-1500-000-99
110	115,00	0,40	110	0,55	0,08	5,84	10	24005110-1000-000-99
110	115,00	0,40	110	0,55	0,08	8,76	15	24005110-1500-000-99

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 04.11.2026

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
115	120,00	0,40	115	0,55	0,08	6,10	10	24005115-1000-000-99
115	120,00	0,40	115	0,55	0,08	9,15	15	24005115-1500-000-99
120	125,00	0,40	120	0,50	0,07	6,36	10	24005120-1000-000-99
120	125,00	0,40	120	0,50	0,07	9,54	15	24005120-1500-000-99
125	130,00	0,40	125	0,50	0,07	6,62	10	24005125-1000-000-99
125	130,00	0,40	125	0,50	0,07	9,92	15	24005125-1500-000-99
140	145,00	0,40	140	0,40	0,06	7,39	10	24005140-1000-000-99
140	145,00	0,40	140	0,40	0,06	11,09	15	24005140-1500-000-99
150	155,00	0,40	150	0,30	0,06	7,91	10	24005150-1000-000-99
150	155,00	0,40	150	0,30	0,06	11,87	15	24005150-1500-000-99
160	165,00	0,40	160	0,28	0,06	8,43	10	24005160-1000-000-99
160	165,00	0,40	160	0,25	0,06	12,64	15	24005160-1500-000-99
180	185,00	0,40	180	0,22	0,05	9,46	10	24005180-1000-000-99
180	185,00	0,40	180	0,22	0,05	14,20	15	24005180-1500-000-99
200	206,00	0,40	200	0,20	0,04	11,25	10	24005200-1000-000-99
200	206,00	0,40	200	0,20	0,04	16,88	15	24005200-1500-000-99
215	221,00	0,40	215	0,20	0,04	12,08	10	24005215-1000-000-99
215	221,00	0,40	215	0,20	0,04	18,12	15	24005215-1500-000-99
225	231,00	0,40	225	0,15	0,03	18,95	15	24005225-1500-000-99
225	231,00	0,40	225	0,15	0,03	12,63	10	24005225-1000-000-99
250	256,00	0,40	250	0,15	0,03	14,01	10	24005250-1000-000-99
250	256,00	0,40	250	0,15	0,03	21,02	15	24005250-1500-000-99
280	286,00	0,40	280	0,10	0,02	15,67	10	24005280-1000-000-99
300	306,00	0,40	300	0,10	0,02	16,77	10	24005300-1000-000-99
315	321,00	0,40	315	0,08	0,02	19,93	10	24005315-1000-000-99
315	321,00	0,40	315	0,08	0,02	29,89	15	24005315-1500-000-99
325	331,00	0,40	325	0,07	0,02	24,18	10	24005325-1000-000-99
350	356,00	0,40	350	0,06	0,02	22,11	10	24005350-1000-000-99
400	406,00	0,40	400	0,04	0,01	25,24	10	24005400-1000-000-99
450	456,00	0,40	450	0,04	0,01	28,36	10	24005450-1000-000-99
500	506,00	0,40	500	0,03	0,01	31,48	10	24005500-1000-000-99
508	514,00	0,40	508	0,02	0,01	31,98	10	24005508-1000-000-99
550	558,00	0,40	550	0,02	0,01	0,00	10	24005550-1000-000-99

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 04.11.2026