

PS-ANTISTATIC

Lightweight and highly flexible PVC hot-air hose, antistatic

Applications	extraction systems, air supply, air extraction, drying, construction drying
Structure	PVC coated polyester fabric, black, opaque, steel wire / spring steel wire / not coated / galvanized
Temperature	-25°C up to 70°C
Properties	excellent flexibility, permanently antistatic ($R < 10^6 \text{ Ohm}$), flame-retardant, with outer wearstrip profile, compressible
Norms	flame-retardant according to DIN 4102 / B1
Optional	- with end rings welded at both ends



Inner Diameter (mm)	Total Weight per Piece (kg)	Length (m)	Article Number
250	6,10	5	09805250-0500-000-00
250	9,15	7,5	09805250-0750-000-00
250	12,20	10	09805250-1000-000-00
300	14,20	10	09805300-1000-000-00
300	7,10	5	09805300-0500-000-00
300	10,65	7,5	09805300-0750-000-00
400	16,52	5	09805400-0500-000-00
400	17,70	7,5	09805400-0750-000-00
400	23,60	10	09805400-1000-000-00
500	14,70	5	09805500-0500-000-00
500	22,05	7,5	09805500-0750-000-00
500	29,40	10	09805500-1000-000-00
600	23,85	5	09805600-0500-000-00
600	35,78	7,5	09805600-0750-000-00
600	47,70	10	09805600-1000-000-00
700	40,95	7,5	09805700-0750-000-00
700	27,30	5	09805700-0500-000-00