FLEXADUX® P1 L PU SE HP

Very lightweight and highly flexible polyurethane spiral hose, with a hollow-profile spiral

Applications sweepers, municipal services, leaf extraction, extraction systems

Structure Polyether-Polyurethane, transparent, profile helix / hollow profile helix

Temperature -40°C up to 100°C, short term up to 125°C

Properties good abrasion resistance,with outer wearstrip profile,hydrolysis & microbe resistant weather proof,flame-retardant,crush-resistant can be driven over







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
60	77,00	0,40	40	0,40	0,20	6,60	10	15352060-1000-000-00
60	77,00	0,40	45	0,35	0,15	9,90	15	15352060-1500-000-00
65	82,00	0,40	45	0,35	0,15	10,43	15	15352065-1500-000-00
65	82,00	0,40	45	0,35	0,15	6,95	10	15352065-1000-000-00
75	92,00	0,40	54	0,30	0,10	7,84	10	15352075-1000-000-00
75	92,00	0,40	54	0,30	0,10	11,76	15	15352075-1500-000-00
80	97,00	0,40	70	0,25	0,10	8,36	10	15352080-1000-000-00
80	97,00	0,40	70	0,25	0,10	12,54	15	15352080-1500-000-00
100	117,00	0,40	75	0,20	0,09	11,41	10	15352100-1000-000-00
100	117,00	0,40	75	0,20	0,09	17,12	15	15352100-1500-000-00
120	137,00	0,40	85	0,20	0,08	13,53	10	15352120-1000-000-00
120	137,00	0,40	85	0,20	0,08	20,30	15	15352120-1500-000-00
125	142,00	0,40	90	0,20	0,08	21,15	15	15352125-1500-000-00
125	142,00	0,40	90	0,20	0,08	14,09	10	15352125-1000-000-00
150	167,00	0,40	105	0,10	0,06	16,70	10	15352150-1000-000-00
150	167,00	0,40	105	0,10	0,06	25,05	15	15352150-1500-000-00

Ocono Ruhrkunststoff GmbH | Weseler Str. 35 | 45478 Mülheim an der Ruhr | Germany | T +49 208 99910 | rk@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026