

EXXHAUST

Light weight and very flexible exhaust hose of TPE-coated Polyester fabric

- Applications** exhaust gas extraction, extraction systems, automotive engineering, vehicle construction, venting
- Structure** coated fabrics / TPE coated polyester fabric, black / jet black (similar RAL 9005), profile helix / hollow profile helix
- Temperature** -40°C up to 200°C
*with proper exhaust gas routing and sufficient fresh air supply (approx. 50%).
- Properties** very good flexibility, very good temperature resistance, with outer wearstrip profile, good oil & petrol resistance, very good chemical resistance



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------|-----------------------------|------------|----------------------|
| 51 | 68,00 | 0,40 | 48 | 0,40 | 1,65 | 5 | 29605051-0500-000-77 |
| 51 | 68,00 | 0,40 | 48 | 0,40 | 2,47 | 7,5 | 29605051-0750-000-77 |
| 51 | 68,00 | 0,40 | 48 | 0,40 | 4,95 | 15 | 29605051-1500-000-77 |
| 51 | 68,00 | 0,40 | 48 | 0,40 | 3,80 | 10 | 29605051-1000-000-77 |
| 63 | 80,00 | 0,40 | 53 | 0,28 | 2,03 | 5 | 29605063-0500-000-77 |
| 63 | 80,00 | 0,40 | 53 | 0,28 | 4,80 | 10 | 29605063-1000-000-77 |
| 63 | 80,00 | 0,40 | 53 | 0,28 | 3,04 | 7,5 | 29605063-0750-000-77 |
| 63 | 80,00 | 0,40 | 53 | 0,28 | 6,09 | 15 | 29605063-1500-000-77 |
| 76 | 93,00 | 0,40 | 60 | 0,17 | 2,44 | 5 | 29605076-0500-000-77 |
| 76 | 93,00 | 0,40 | 60 | 0,17 | 3,66 | 7,5 | 29605076-0750-000-77 |
| 76 | 93,00 | 0,40 | 60 | 0,17 | 7,32 | 15 | 29605076-1500-000-77 |
| 76 | 93,00 | 0,40 | 60 | 0,17 | 5,40 | 10 | 29605076-1000-000-77 |
| 102 | 119,00 | 0,40 | 71 | 0,05 | 7,10 | 10 | 29605102-1000-000-77 |
| 102 | 119,00 | 0,40 | 71 | 0,05 | 3,27 | 5 | 29605102-0500-000-77 |
| 102 | 119,00 | 0,40 | 71 | 0,05 | 4,90 | 7,5 | 29605102-0750-000-77 |
| 102 | 119,00 | 0,40 | 71 | 0,05 | 9,80 | 15 | 29605102-1500-000-77 |
| 102 | 119,00 | 0,40 | 71 | 0,05 | 13,07 | 20 | 29605102-2000-000-77 |
| 127 | 144,00 | 0,40 | 100 | 0,04 | 8,70 | 10 | 29605127-1000-000-77 |
| 127 | 144,00 | 0,40 | 100 | 0,04 | 4,06 | 5 | 29605127-0500-000-77 |
| 127 | 144,00 | 0,40 | 100 | 0,04 | 6,09 | 7,5 | 29605127-0750-000-77 |
| 127 | 144,00 | 0,40 | 100 | 0,04 | 12,19 | 15 | 29605127-1500-000-77 |
| 152 | 169,00 | 0,40 | 110 | 0,03 | 7,29 | 7,5 | 29605152-0750-000-77 |

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------|-----------------------------|------------|----------------------|
| 152 | 169,00 | 0,40 | 110 | 0,03 | 14,57 | 15 | 29605152-1500-000-77 |
| 152 | 169,00 | 0,40 | 110 | 0,03 | 10,40 | 10 | 29605152-1000-000-77 |
| 152 | 169,00 | 0,40 | 110 | 0,03 | 4,86 | 5 | 29605152-0500-000-77 |
| 203 | 220,00 | 0,40 | 155 | 0,01 | 6,48 | 5 | 29605203-0500-000-77 |
| 203 | 220,00 | 0,40 | 155 | 0,01 | 9,72 | 7,5 | 29605203-0750-000-77 |
| 203 | 220,00 | 0,40 | 155 | 0,01 | 13,70 | 10 | 29605203-1000-000-77 |
| 203 | 220,00 | 0,40 | 155 | 0,01 | 19,44 | 15 | 29605203-1500-000-77 |